

Amendments to the Specification

At page 1, prior to the Technical Field section, please enter the following new paragraph.

RELATED PATENT DATA

This application claims priority to Patent Cooperation Treaty application Serial No. PCT/SG2003/000292, which was filed December 24, 2003, and which claims priority to Singapore Application Serial No. 200207824-4, which was filed December 27, 2002.

Please replace the paragraph beginning at line 17 of page 4 with the following new paragraph.

Preferably said at least one panel and said extension panel are in an edge to edge juxtaposition to each other when in the expanded condition without any significant gap ~~existing~~ existing between said at least one panel and said extension panel.

Please replace the paragraph beginning at line 24 of page 4 with the following new paragraph.

In a further aspect the present invention consist in a mobile first aid post comprising

a road vehicle

a compartment carried by said vehicle, defining a generally boxed shaped openable enclosure for housing medical supplies and equipment, said compartment including a fixed structure and at least one rigid movable panel which is movable relative to said fixed structure between a condition closing a side of said enclosure (hereinafter "closed condition") wherein said panel defines at least part of a side wall of said enclosure and an erected condition wherein said at least one panel is in a substantially or near horizontal condition and thereby creating an opening for said enclosure, said at least one panel movable in a pivoting manner to said fixed structure to extend outwardly from said enclosure and above said opening to provide a region covered overhead by said at least one panel for a person positioned adjacent said side of said vehicle where said at least one panel is provided and positioned when in said erected condition,

said panel providing an opening to said enclosure when in said erected condition which extends substantially to a floor of said enclosure

a seat structure pivotably mounted to said fixed ~~structure~~ structure proximate or at said floor to, in a first pivotal condition present a substantially horizontal support surface above the surface of said floor to allow a person within said enclosure to be sedentary thereon and in a second pivotal condition different to the first, present a substantially horizontal surface intermediate of said floor and the ground adjacent said vehicle to allow a person to be supported thereon.